

## TREATING MOGOGO'S BHP TABLETOP

---

Wipe the BHP tabletop with a cloth and lukewarm water.  
Wipe the surface with a soft dry cloth.

For a more thorough cleaning, you can use a few drops of dishwashing liquid or a common cleaning solution without abrasive agent.

Wipe it afterwards with a clean, moist cloth and finally with a clean, dry cloth.

Do not use scouring powder or nylon sponges as these will fade or scratch the laminate.

### **Contaminations/Stains**

The material is resistant to most household chemicals. Although liquids cannot penetrate into the material, contaminations or stains should be wiped off immediately. Longer contact with mainly acidic substances e.g. aggressive household cleaner, metal cleaner, toilet cleaner and certain oven cleaner should be avoided. In the case of special contamination, please clean the surface with pure hot water.

### **Paraffin or wax residues**

Residues of paraffin or wax shall at first be mechanically removed, using a plastic or wood spatula.

Scratching the surface must be avoided. Remaining residues can be ironed with a sheet of blotting paper.

### **Water-soluble dyes, lacquers, adhesives and dispersions**

Fresh contaminations usually can be cleaned with warm water. Dried residues can be cleaned using solvents like ethanol, acetone, benzine or nail-varnish remover.

### **Solvent-based dyes, lacquers and adhesives**

Fresh contaminations usually can be cleaned with solvents, dried residues if necessary after a longer application time. Suitable solvents must be inquired from dye-, lacquer- or adhesive supplier.

### **Component adhesives and lacquers**

An example of 2 component adhesives are condensation resins (adhesives) based on formaldehyde, urea (UF), melamine (MF), phenol (PF) and resorcinol. Examples of reactive systems are epoxy resin, unsaturated polyester and polyurethane (PU). Contaminations of these types can not be removed from the laminate surface after hardening. The surface must immediately be cleaned with suitable organic solvents, recommended by the supplier of the adhesive/lacquer system.

### **Sealing material based on silicone or polyurethane**

Residues shall at first be mechanically removed using a plastic or wood spatula. Scratching the surface must be avoided!

Remaining residues can be cleaned with a silicone remover, if necessary after a longer application time.

Longer contact times with the silicone remover can change the laminate surface.

### **Streaking after cleaning with solvents**

Streaking can be removed through subsequent cleaning with hot water and drying with a clean, soft, absorbent cloth or a household-type paper tissue.

In case of any light damage to the bamboo-core edge, sand it gently and spread a subtle amount of furniture oil.